

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently Amended) A composition for use as an additive for fuels or lubricants comprising a reaction product of a treated amine and a compound selected from the group consisting of hydrocarbyl succinic anhydrides, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups, and copolymers of unsaturated acids and polyolefins, wherein the reaction product is oil soluble and has a number average molecular weight ranging from about 900 to about 50,000 as determined by gel permeation chromatography, and wherein the treated amine comprises an aliphatic or aromatic amine containing at least one primary or secondary amino group reacted with acrylonitrile or at least one homologue thereof, followed by reduction to the primary amine,

with the proviso that the aliphatic amine is chosen from aminoguanidine bicarbonate, diethylene triamine, triethylene tetramine, tetraethylene pentamine, and pentaethylene hexamine, heavy polyamines and hydroxyamines,

with the proviso that the aromatic amine is chosen from N-arylphenylenediamines; and

with the further proviso that if the aliphatic ~~or aromatic~~-amine is a hydroxyamine, the hydroxyamine is chosen from oligomers, polymers, aminoethylethanolamine, aminopropyldiethanolamine, partially propoxylated hexamethylene diamine, 3-amino-1,2-propanediol, tris(hydroxymethyl)aminomethane, and 2-amino-1,3-propanediol; ~~and~~

~~with the further proviso that the aliphatic amine is chosen from aminoguanidine bicarbonate, diethylene triamine, triethylene tetramine, tetraethylene pentamine, pentaethylene hexamine and heavy polyamines.~~

2. (Previously Presented) The composition of claim 1, wherein the aliphatic or aromatic amine is reacted with one to five equivalents of acrylonitrile or one of its

homologues, followed by reduction of the primary amine per primary or secondary amino group in the amine.

3. (Previously Presented) The composition of claim 1, wherein the amine is a substantially linear aliphatic amine.

4. (Previously Presented) The composition of claim 1, wherein the amine is an aromatic amine.

5. (Previously Presented) The composition of claim 1, wherein the reaction product comprises a hydrocarbyl-substituted succinimide derived from the treated amine and a hydrocarbyl-substituted succinic acid having a mole ratio of succinic acid to treated amine ranging from about 0.3:1.0 to about 12.0:1.

6. (Cancelled)

7. (Cancelled)

8. (Previously Presented) The composition of claim 1, wherein the reaction product further comprises an untreated amine selected from the group consisting of aliphatic amines and aromatic amines.

9. (Previously Presented) A lubricant composition comprising an oil of lubricating viscosity and from about 0.1 to 10 wt. %, based on the total weight of the composition of the reaction product of claim 1.

10. (Previously Presented) A vehicle having moving parts and containing a lubricant for lubricating the moving parts, the lubricant comprising an oil of lubricating viscosity and from about 0.1 to 10 wt. %, based on the total weight of the lubricant composition, of the reaction product of claim 1.

11. (Previously Presented) An additive package for lubricants or fuels comprising a reaction product of claim 1 and a composition selected from the group consisting of hydrocarbyl succinic anhydrides reacted with an amine, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes and amines, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups reacted with amines, copolymers of unsaturated acids and polyolefins reacted with amines, and acid or ester functionalized hydrocarbon polymers reacted with amines, wherein the amines comprise untreated aliphatic or aromatic amines.

12. (Previously Presented) A lubricant composition comprising an oil of lubricating viscosity and from about 0.1 to 10 wt. %, based on the total weight of the lubricant composition, of the additive of claim 11.

13. (Previously Presented) A fuel composition comprising a hydrocarbyl fuel and from about 5 to about 200 pounds per thousand barrels of the composition of claim 1.

14. (Currently Amended) A lubricant additive comprising a reaction product of a treated amine and a compound selected from the group consisting of hydrocarbyl succinic anhydrides, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups, and copolymers of unsaturated acids and polyolefins, wherein the reaction product is oil soluble and has a number average molecular weight ranging from about 900 to about 50,000 as determined by gel permeation chromatography, and wherein the treated amine comprises an aliphatic or aromatic amine containing at least one primary or secondary amino group reacted with acrylonitrile or one of its homologues, followed by reduction to the primary amine, with the proviso that the aliphatic amine is chosen from aminoguanidine bicarbonate, diethylene triamine, triethylene tetramine, tetraethylene pentamine, and pentaethylene hexamine, heavy polyamines and hydroxyamines, with the proviso that the aromatic amine is chosen from N-arylphenylenediamines; and

with the further proviso that if the aliphatic ~~or aromatic~~-amine is a hydroxyamine, the hydroxyamine is chosen from oligomers, polymers, aminoethylethanolamine, aminopropyldiethanolamine, partially propoxylated hexamethylene diamine, 3-amino-1,2-propanediol, tris(hydroxymethyl)aminomethane, and 2-amino-1,3-propanediol.

15. (Previously Presented) The lubricant additive of claim 14, wherein the reaction product further comprises an untreated amine selected from the group consisting of aliphatic and aromatic amines.

16. (Currently Amended) The lubricant additive of claim 14, further comprising a composition selected from the group consisting of hydrocarbyl succinic anhydrides reacted with amines, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes ~~formaldehydes~~ and amines, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups reacted with amines, copolymers of unsaturated acids and polyolefins reacted with amines, and acid or ester functionalized hydrocarbon polymers reacted with amines, wherein the amines comprise untreated aliphatic or aromatic amines.

17. (Previously Presented) The lubricant additive of claim 14, wherein the reaction product is a post treated reaction product.

18. (Previously Presented) A lubricant composition comprising an oil of lubricating viscosity and from about 0.1 to 10 wt. %, based on the total weight of the lubricant composition, of the lubricant additive of claim 14.

19. (Currently Amended) A fuel additive comprising a reaction product of a treated amine and a compound selected from the group consisting of hydrocarbyl succinic anhydrides, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups, copolymers of unsaturated acids and polyolefins, wherein the reaction product is oil soluble and has a number average molecular weight

ranging from about 900 to about 50,000 as determined by gel permeation chromatography, and wherein the treated amine comprises ~~an~~ a linear or branched aliphatic or an aromatic amine containing at least one primary or secondary amino group reacted with acrylonitrile or at least one homologue thereof, followed by reduction to the primary amine

with the proviso that the aliphatic amine is chosen from aminoguanidine bicarbonate, diethylene triamine, triethylene tetramine, tetraethylene pentamine, and pentaethylene hexamine, heavy polyamines and hydroxyamines,

with the proviso that the aromatic amine is chosen from N-arylphenylenediamines; and

with the further proviso that if the aliphatic amine is a hydroxyamine, the hydroxyamine is chosen from oligomers, polymers, aminoethylethanolamine, aminopropyldiethanolamine, partially propoxylated hexamethylene diamine, 3-amino-1,2-propanediol, tris(hydroxymethyl)aminomethane, and 2-amino-1,3-propanediol.

20. (Previously Presented) The fuel additive of claim 19, wherein the reaction product further comprises an untreated amine selected from the group consisting of aliphatic and aromatic amines.

21. (Previously Presented) The fuel additive of claim 19, further comprising a composition selected from the group consisting of hydrocarbyl succinic anhydrides reacted with amines, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes and amines, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups reacted with amines, copolymers of unsaturated acids and polyolefins reacted with amines, and acid or ester functionalized hydrocarbon polymers reacted with amines, wherein the amines comprise untreated aliphatic or aromatic amines.

22. (Previously Presented) The fuel additive of claim 19, wherein the reaction product is a post treated reaction product.

23. (Currently Amended) A fuel composition comprising a fuel and from about 5 to 200 pounds per thousand barrels of the ~~lubricant~~ fuel additive of claim 14 19.

24. (Currently Amended) A method of lubricating moving parts of a vehicle, the method comprising using as a lubricating oil for one or more moving parts of the vehicle a lubricant composition containing a lubricant and a lubricant additive, the lubricant additive including a reaction product of treated amine and a compound selected from the group consisting of hydrocarbyl succinic anhydrides, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups, copolymers of unsaturated acids and polyolefins, wherein the reaction product is oil soluble and has a number average molecular weight ranging from about 900 to about 50,000 as determined by gel permeation chromatography, and wherein the treated amine comprises an aliphatic or aromatic amine containing at least one primary or secondary amino group reacted with acrylonitrile or a homologue thereof, followed by reduction to the primary amine,

with the proviso that the aliphatic amine is chosen from aminoguanidine bicarbonate, diethylene triamine, triethylene tetramine, tetraethylene pentamine, and pentaethylene hexamine, heavy polyamines and hydroxyamines,

with the proviso that the aromatic amine is chosen from N-arylphenylenediamines; and

with the further proviso that if the aliphatic ~~or aromatic~~ amine is a hydroxyamine, the hydroxyamine is chosen from oligomers, polymers, aminoethylethanolamine, aminopropyldiethanolamine, partially propoxylated hexamethylene diamine, 3-amino-1,2-propanediol, tris(hydroxymethyl)aminomethane, and 2-amino-1,3-propanediol.

25. (Previously Presented) The method of claim 24 wherein the vehicle includes an internal combustion engine having a crankcase and wherein the lubricant composition comprises a crankcase oil present in the crankcase of the vehicle.

26. (Previously Presented) The method of claim 24 wherein the lubricant composition comprises a drive train lubricant present in an automotive drive train of the vehicle.

27. (Previously Presented) The method of claim 24, wherein the reaction product includes an untreated amine selected from the group consisting of aliphatic and aromatic amines.

28. (Previously Presented) The method of claim 24, wherein the lubricant additive includes a composition selected from the group consisting of hydrocarbyl succinic anhydrides reacted with amines, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes and amines, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups reacted with amines, copolymers of unsaturated acids and polyolefins reacted with amines, and acid or ester functionalized hydrocarbon polymers reacted with amines, wherein the amines comprise untreated aliphatic or aromatic amines.

29. (Previously Presented) The method of claim 24, wherein the reaction product is a post treated reaction product.

30. (Currently Amended) A method for lubricating moving parts comprising contacting the moving parts with a lubricant composition containing a lubricant and a lubricant additive, the lubricant additive comprising a reaction product of a treated amine and a compound selected from the group consisting of hydrocarbyl succinic anhydrides, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups, copolymers of unsaturated acids and polyolefins, wherein the reaction product is oil soluble and has a number average molecular weight ranging from about 900 to about 50,000 as determined by gel permeation chromatography, and wherein the treated amine comprises an aliphatic or aromatic amine containing at least

one primary or secondary amino group reacted with acrylonitrile or homologue thereof, followed by reduction to the primary amine,

with the proviso that the aliphatic amine is chosen from aminoguanidine bicarbonate, diethylene triamine, triethylene tetramine, tetraethylene pentamine, and pentaethylene hexamine, heavy polyamines and hydroxyamines,

with the proviso that the aromatic amine is chosen from N-arylphenylenediamines; and

with the further proviso that if the aliphatic ~~or aromatic~~ amine is a hydroxyamine, the hydroxyamine is chosen from oligomers, polymers, aminoethylethanolamine, aminopropyldiethanolamine, partially propoxylated hexamethylene diamine, 3-amino-1,2-propanediol, tris(hydroxymethyl)aminomethane, and 2-amino-1,3-propanediol.

31. (Previously Presented) The method of claim 30 wherein the lubricant composition comprises a gear lubricant present in a gear box.

32. (Previously Presented) The method of claim 30, wherein the reaction product includes an untreated amine selected from the group consisting of aliphatic and aromatic amines.

33. (Previously Presented) The method of claim 30, wherein the lubricant additive includes a composition selected from the group consisting of hydrocarbyl succinic anhydrides reacted with amines, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes and amines, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups reacted with amines, copolymers of unsaturated acids and polyolefins reacted with amines, and acid or ester functionalized hydrocarbon polymers reacted with amines, wherein the amines comprise untreated aliphatic or aromatic amines.

34. (Previously Presented) The method of claim 30, wherein the reaction product is a post treated reaction product.



35. (Currently Amended) A method for decreasing combustion chamber deposits and/or intake valve deposits in an engine comprising providing a fuel containing an additive comprising a reaction product of a treated amine and a compound selected from the group consisting of hydrocarbyl succinic anhydrides, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups, copolymers of unsaturated acids and polyolefins, wherein the reaction product is oil soluble and has a number average molecular weight ~~raning~~ ranging from about 900 to about 50,000 as determined by gel permeation chromatography, and wherein the treated amine comprises an a linear or branched aliphatic or an aromatic amine containing at least one primary or secondary amino group reacted with acrylonitrile or a homologue thereof, followed by reduction to the primary amine.

36. (Previously Presented) The method of claim 35, wherein the reaction product includes an untreated amine selected from the group consisting of aliphatic and aromatic amines.

37. (Previously Presented) The method of claim 35, wherein the diesel fuel includes a composition selected from the group consisting of hydrocarbyl succinic anhydrides reacted with amines, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes and amines, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups reacted with amines, copolymers of unsaturated acids and polyolefins reacted with amines, and acid or ester functionalized hydrocarbon polymers reacted with amines, wherein the amines comprise untreated aliphatic or aromatic amines.

38. (Previously Presented) The method of claim 35, wherein the reaction product is a post treated reaction product.

39. (Previously Presented) The lubricating composition of claim 9, wherein the composition has a sulfur content of less than 0.5 weight percent, a phosphorus content

of less than 0.11 weight percent, and a sulfated ash content of less than 1.2 weight percent.

40. (New) A fuel composition comprising:

a hydrocarbyl fuel; and

a reaction product of a treated amine and a compound selected from the group consisting of hydrocarbyl succinic anhydrides, Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes, ethylene-propylene copolymers grafted with ethylenically unsaturated carboxylic groups, copolymers of unsaturated acids and polyolefins, wherein the reaction product is oil soluble and has a number average molecular weight ranging from about 900 to about 50,000 as determined by gel permeation chromatography, and wherein the treated amine comprises a linear or branched aliphatic or an aromatic amine containing at least one primary or secondary amino group reacted with acrylonitrile or at least one homologue thereof, followed by reduction to the primary amine, wherein the reaction product is in an amount effective for decreasing combustion chamber deposits resulting from combustion of the fuel as compared to combustion of a fuel devoid of the reaction product.

41. (New) The fuel composition of claim 40, wherein the hydrocarbyl fuel is a diesel fuel.

42. (New) A composition for use as an additive for fuels or lubricants comprising a reaction product of a treated amine and a compound selected from the group consisting of hydrocarbyl succinic anhydrides and Mannich adducts derived from hydrocarbyl-substituted phenols reacted with formaldehydes, wherein the reaction product is oil soluble and has a number average molecular weight ranging from about 900 to about 50,000 as determined by gel permeation chromatography, and wherein the treated amine comprises an aliphatic or aromatic amine containing at least one primary or secondary amino group reacted with acrylonitrile or at least one homologue thereof, followed by reduction to the primary amine,

with the proviso that the aliphatic amine is chosen from aminoguanidine bicarbonate, diethylene triamine, triethylene tetramine, tetraethylene pentamine, and pentaethylene hexamine, heavy polyamines and hydroxyamines,

with the further proviso that if the aliphatic amine is a hydroxyamine, the hydroxyamine is chosen from oligomers, polymers, aminoethylethanolamine, aminopropyldiethanolamine, partially propoxylated hexamethylene diamine, 3-amino-1,2-propanediol, tris(hydroxymethyl)aminomethane, and 2-amino-1,3-propanediol.

43. (New) The composition of claim 42, wherein the reaction product comprises a hydrocarbyl-substituted succinimide derived from the treated amine and a hydrocarbyl-substituted succinic acid having a mole ratio of succinic acid to treated amine ranging from about 0.3:1.0 to about 12.0:1.

44. (New) The composition of claim 1, wherein the reaction product comprises Mannich adducts derived from hydrocarbyl-substituted phenols, formaldehydes and treated amines.